


IP-3ETI23

Socket 370 ATX Board for Pentium® !!! / Celeron™ Processor with VGA / LAN / Audio

Key-point:

- > Socket 370 for Intel® Pentium® !!! / Celeron™ Processor, up to 1.4GHz
- > Intel® 815E Chipsets, 100 / 133 MHz FSB
- > Chipset integrated VGA function
- > Intel® 82562EM controller, Support 10 / 100 Base-TX Ethernet
- > Realtek® ALC650 AC97 Audio
- > 2 x COM ports / 4 x USB ports, 1 x AGP / 4 x PCI / 3 x ISA slots
- > WatchDog Timer & Hardware monitoring function



Specifications:

- ⊙ **Processor:**
 - * Support Intel® Socket 370 Pentium® !!! / Celeron™ Processor
 - * Up to 1.4GHz
- ⊙ **Core Logic:**
 - * Intel® 815E + ICH2 chipsets
- ⊙ **BIOS:**
 - * Award BIOS
- ⊙ **Front Side Bus Speed:**
 - * 100 / 133 MHz
- ⊙ **Memory:**
 - * Two 168-pins DIMM support 512MB SDRAM (max.)
- ⊙ **Onboard VGA Controller:**
 - * 815E chipset integrated VGA function
 - * 15 Pins VGA connector
- ⊙ **LAN Controller:**
 - * Intel® 82562EM, for 10 / 100 Base-TX Ethernet
- ⊙ **Audio Controller:**
 - * Realtek® ALC650 AC97 Audio
- ⊙ **Onboard IDE:**
 - * Two EIDE channels for PIO Mode, DMA Mode
 - * Supports four ATA 100/66/33 IDE devices
- ⊙ **Multi I/O:**
 - Onboard Winbond® W83627HF chip, Support:
 - * 1 x IrDA by 5-pin pin-header,
 - * 1x Floppy Interface,
 - * 1 x SPP / EPP / ECP parallel port
 - * COM1/2: RS-232
- ⊙ **Keyboard / Mouse Connector:**
 - * Staked connector for PS/2 type keyboard /mouse
 - * 1 x 6-pins connector for external keyboard & mouse
- ⊙ **USB:**
 - * Support 4 x USB ports
 - * 2 x USB ports by pin-headers
- ⊙ **WatchDog Timer:**
 - * 256 Levels software programmable
- ⊙ **Hardware Monitoring:**
 - * Winbond® W83627HF chip, Monitoring for CPU and system temperature, voltage and fan speed
- ⊙ **Environments:**
 - * Operation temperature: 0°C to 60°C (32° F to 140° F)
 - * Storage temperature: -20°C to 80°C (-68° F to 176° F)
 - * Relative humidity: 10% to 90% (Non-Condensing)
- ⊙ **Extension slot:**
 - * 1 x AGP slot
 - * 4 x PCI slots
 - * 3 x ISA slots
- ⊙ **Certification:**
 - * CE, FCC Approval
- ⊙ **Others features**
 - * ITE® 8888 PCI to ISA bridge
- ⊙ **Form Factor:**
 - * ATX form factor 12" x 8.3" (305mm x 210mm)

*Specification is subject to change without prior notice

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support Audio	Support LAN	Support AGP/PCI/ISA
IP-3ETI23	Standard Product	---	Yes	Yes	Yes	1 / 4 / 3

I/O Shield Layout

