



# UNICORN COMPUTER CORP.

ADD : 3FL-4., No. 130, Chien-Kung Rd., Chung-Ho City, Taipei Hsien, Taiwan 235

TEL : 886-2-2223-6699 • 2223-6655 FAX : 886-2-2222-1269

Web Site : [www.unicorn-computer.com.tw](http://www.unicorn-computer.com.tw)

E-Mail : [sales@unicorn-computer.com.tw](mailto:sales@unicorn-computer.com.tw) • [support@unicorn-computer.com.tw](mailto:support@unicorn-computer.com.tw)

## ENDAT-5701

### Specifications

#### CPU Support:

Support 7 / Super 7 for Intel Pentium CPU, MMX; AMD K5 / K6 / K6-2 / K6-3; IDT C6; Rise; IBM / Cyrix 6X86 Compatible CPUs up to 500MHz

#### Chipset:

VIA MVP4 VT8501 66/100MHz North Bridge with integrated Trident 2X AGP Graphic controller and VT82C686A Super I/O

#### BIOS:

AWARD Flash BIOS

#### System Memory:

Two DIMM sockets accept up to 512MB SDRAM support PC-66/PC-100 frequency

#### Enhanced IDE interface:

Two 40-pin box header support up to 2 EIDE devices, Ultra DMA transfer 33/66 mode and BIOS auto-detect

#### FDD interface:

Support up to two Floppy Disk Drives

#### Display Controller:

- Chipset: On VT8501 chip integrated 2X AGP Graphic controller with SMA up to 8MB
- Display Type: CRT; 24bit TFT interface LCD panel
- LCD panel resolution: 640 x 480; 800 x 600; 1024 x 768

#### Audio Controller: (optional)

- Chipset: VIA VT82C686A, AC'97 2.0 compliant, Multi-Stream Direct Sound and Direct Sound 3D acceleration
- Interface: Line In, CD In, MIC In, Speaker Out (optional)

#### High Speed Multi I/O:

- **Chipset:** VIA VT82C686A integrated Super I/O
- **Serial Ports:** 4 high speed RS-232 ports with 1 high speed RS-232/422/485 port (via COM2 as option), all 4 serial ports support 16C550 UART and 16 byte FIFO, and with +5V, +12V power selector
- **Parallel Ports:** 1 Bi-directional parallel ports support SPP/EPP/ECP mode
- **USB Ports:** 2 ports with 1.1 compliant
- **Infrared Port:** 1 IrDA TX/RX port with pin header
- **Keyboard / Mouse Connectors:** Support PS/2 keyboard and mouse with reserved pin header on board

#### Network Interface:

- Chipset: 1 x Realtek 8139C
- 10/100 BaseT / TX support, full duplex with RJ 45 connector on board
- Compliant with IEEE 802.3X
- Boot from LAN function

#### On board solid State Disk Interface:

One DOC 2000 socket support M-System DiskOnChip

#### Power management:

Supports power saving modes including APM 1.2 compliant

#### Real Time Clock:

On chip RTC with external Li Battery back up

#### On board Bus Expansion:

188-pin connectors with PCI and ISA signal for expansion up to 3 PCI slots and 3 ISA slots

#### Board Dimension:

LPX form factor, 220 x 220 mm

#### Power Types:

Support AT and ATX power supply by jumper selection

#### Operating Temperature: 0 ~ 60°C

### Ordering Information:

#### Standard:

<b>ENDAT-5701</b>	Support CRT display only
<b>ENDAT-5701-1</b>	Support 24bit TFT LCD panel

#### Audio Kit Options:

<b>AV Card</b>	with 3W amplifier + bracket
<b>UC-A001</b>	with 3W amplifier
<b>UC-A002</b>	without 3W amplifier

#### Supported LCD Kits:

<b>UC-T1848</b>	Support dual channels 36bit, 48bit TTL LCD panel
<b>UC-LT1815</b>	Support single channel 18bit, 24bit LVDS LCD panel
<b>UC-L1836</b>	Support dual channel 36bit LVDS LCD panel
<b>UC-L2448</b>	Support dual channel 48bit LVDS LCD panel