

M845B/VE+

Socket 478 ATX Board for Pentium® 4 / Celeron™ Processor with VGA / LAN

Key-point:

- > Socket 478 for Intel® Pentium® 4 / Celeron™ Processor, up to 3.06GHz
- > Intel® 845GV Chipsets, 400 / 533 MHz FSB
- > Chipset integrated VGA function
- > Intel® 82562EM Ethernet, Support 10/100 Base-TX Ethernet
- > 6 x USB 2.0 ports / 4 x COM ports
- > 1 x AGP / 6 x PCI Slots
- > WatchDog Timer & Hardware monitoring function



Specifications:

- ◎ **Processor:**
 - * Support Intel® Socket 478 Pentium® 4 / Celeron™ Processor
 - * Up to 3.06GHz
- ◎ **Core Logic:**
 - * Intel® 845GV + ICH4 chipsets
- ◎ **BIOS:**
 - * Award BIOS
- ◎ **Front Side Bus Speed:**
 - * 400 / 533 MHz
- ◎ **Memory:**
 - * Two 184-pins DIMM support 2GB DDR SDRAM (max.)
- ◎ **Onboard VGA Controller:**
 - * Intel® 845GV chipset integrated VGA function,
 - * AGP slot only support ADD card
- ◎ **LAN Controller:**
 - * Intel® 82562EM, for 10/100 Base-TX Ethernet, support Wake-On-LAN
- ◎ **Onboard IDE:**
 - * Two EIDE channels for PIO Mode, DMA Mode
 - * Supports four ATA 100/66/33 IDE devices
- ◎ **Multi I/O:**
 - Onboard Winbond® W83627HF chip, Support:
 - * 1 x IrDA by 5-pin pin-header,
 - * 1 x Floppy Interface, and one 26-pins foil cable connector for slim Floppy disk drive
 - * 1 x SPP / EPP / ECP parallel port
 - * COM1/2: RS-232
 - * COM3/4: RS-232 or RS-422/485 (jumper selectable)
- ◎ **Keyboard / Mouse Connector:**
 - * Staked connector for PS/2 type keyboard / mouse
 - * 1 x 6-pins connector for external keyboard / mouse
- ◎ **USB:**
 - * Support 6 x USB 2.0 ports
 - * 4 x USB ports by pin-headers, Optional USB cable with bracket
- ◎ **WatchDog Timer:**
 - * 256 Levels software programmable
- ◎ **Hardware Monitoring:**
 - * Winbond® W83627HF chip, Monitoring for CPU and system temperature, voltage and fan speed
- ◎ **Extension slot:**
 - * 1 x AGP slot for ADD card
 - * 6 x PCI slots
- ◎ **Environments:**
 - * Operation temperature: 0°C to 60°C (32° F to 140° F)
 - * Storage temperature: -20°C to 80°C (-68° F to 176° F)
 - * Relative humidity: 10% to 90% (Non-Condensing)
- ◎ **Certification:**
 - * CE, FCC Approval
- ◎ **Others features**
 - * 4 x fan connectors
- ◎ **Form Factor:**
 - * ATX form factor 12" x 8.7" (305mm x 220mm)

*Specification is subject to change without prior notice

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support Audio	Support LAN	Support AGP/PCI /ISA
M845B/VE+	Standard Product	---	Yes	---	Yes	1(ADD) / 6 / 0

I/O Shield Layout

