

# MPC-6010A

4U 14-Slot Chassis with Display Module



DM-84T LCD Module

Analog VGA Input



MPC 6010AW Basic Model (No Display)

## Specifications

- ◆ 4U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect the disk access and on/off power switch
- ◆ LCD Monitor Module

| Models      | DM-64T               | DM-84T               |
|-------------|----------------------|----------------------|
| LCD Type    | 6.4" TFT             | 8.4" TFT             |
| Resolution  | 640 x 480            | 800 x 600            |
| Max. colors | 18 bits              | 18 bits              |
| Brightness  | 300cd/m <sup>2</sup> | 250cd/m <sup>2</sup> |
| Interface   | Analog VGA           | Analog VGA           |
| OSD Control | Yes                  | Yes                  |

- ◆ Drive Bays : 3 x 5.25" Drive  
1 x internal 3.5" HDD  
1 x 3.5" FDD
- ◆ Cooling Fans : Two 8cm ball bearing cooling fans
- ◆ Designed with anti-vibration card clamp to keep system stable
- ◆ Supports ATX form factor PC motherboard
- ◆ Standard equipped with ACE-832A 300W AT power supply
- ◆ Supports Backplane : 14 slot  
PCI-14S3, PCI-14S2, PCI-14S, PX-14S5, PX-14S3, PX-14S2, IP-14S3, IP-14S, BP-14S/SD2/SD/15S, PCI-13SD, IP-13SD, IPX-13S, PCIAGP-13S2, PCIAGP-13S3, PXAGP-12S2, PXAGP-13S, PXAGP-13S3
- ◆ Supports power supply : PS/2 size AT/ATX  
ACE-93x/92x/916V series  
ACE-828/832/840/850 series  
ACE-R30A redundant power supply
- ◆ Optional Slide : 24" or 18"
- ◆ Vibration : 5 ~ 17Hz, 0.1" double amplitude displacement  
17 ~ 640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Operating temperature : 0-50°C
- ◆ Dimension : 431(W) x 176(H) x 528(D)mm; (17" x 6.9" x 20.8")

## Ordering Information

◆ MPC-6010AW ☐ / ☐ / Power Supply / Display / Backplane

ATX:

ATX MB

R: Redundant power supply

ACE-832A  
ACE-832AP  
ACE-R30A

DM-64T-6010  
DM-84T-6010

PCI-14S  
PX-14S  
IP-14S  
...

# MPC-6022A

5U Height 14-Slot Industrial PC Chassis



Analog VGA Input



## Specifications

- ◆ 5U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect disk access, power on/off and reset switch
- ◆ LCD monitor module:
  - 12.1" high Brightness TFT
  - 800x600 resolution
  - Brightness : 350 cd/m<sup>2</sup>
  - LCD interface: Analog VGA Signal input
- ◆ Drive Bays :
  - 1 x 3.5" FDD
  - 1 x 5.25" CD-ROM
  - 1 x 3.5" HDD
- ◆ Two 12cm ball bearing cooling fans
- ◆ Designed with anti-vibration card clamp to keep system stable
- ◆ Supports ATX form factor PC motherboard
- ◆ Optional Backplane :  
PCI-14S3, PCI-14S2, PCI-14S, PX-14S5, PX-14S3, PX-14S2, IP-14S3, IP-14S, BP-14S/SD2/SD/15S, PCI-13SD, IP-13SD, IPX-13S, PCIAGP-13S2, PCIAGP-13S3, PXAGP-12S2, PXAGP-13S, PXAGP-13S3
- ◆ Supports power supply :  
PS/2 size AT/ATX power supply  
ACE-R30A redundant power supply
- ◆ Optional Slide : 24" or 18"
- ◆ Vibration: 5 ~ 17Hz, 0.1" double amplitude displacement  
17 ~ 640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimension : 431(W) x 220(H) x 470(D)mm; (17"x8.7"x18.5")
- ◆ Net/GW: 15/18 (kg)

## Ordering Information

### ◆ MPC-6022AW-R30/ACE-832A

5U 14-slot rackmount chassis with 12.1" LCD and ACE-832A 300W power supply

### ◆ MPC-6022AWR-R30

5U 14-slot rackmount chassis with 12.1" LCD

### ◆ MPC-6022AWATX-R30 /ACE- 832A

5U ATX MB rackmount chassis with 12.1" LCD/ ACE-832A power supply

Single Board Computer

LCD Product Series

Panel PC

Workstation

Rack-Console

Display

LCD-Kit

Touch Screen

Chassis

Power supply

Peripheral