

Eclipse Surge Suppressors

Total protection against power surges, spikes, nearby lightning strikes and line noise*

Advanced Features

- ▶ Up to 1020 joule rating
- ▶ Master On/Off switch
- ▶ Instantaneous response time
- ▶ Visual Alarm(s)
- ▶ Audible Alarm (except Personal)
- ▶ Circuit Breaker and Thermal Fuse Protection
- ▶ 360° Rotating Plug (except Personal)

The **Eclipse** product line brings affordable surge protection to your PC, peripherals and other devices in the event of nearby lightning strikes, surges and spikes. In addition, Eclipse provides line noise reduction to minimize interference from the utility power. All Eclipse models include a "load protected" status LED to notify you in case of surge protection failure. On the EclipsePro and ProTel models, an audible alarm provides warning in combination with the LED.

EclipsePro and ProTel models feature a "ground OK" LED to warn of building wiring faults which can potentially interfere with Eclipse's ability to arrest surges and spikes.

Eclipse is available in three models for individual applications:


- ▶ Eclipse Personal for home appliance or home/office PC use
- ▶ EclipsePro and Eclipse ProTel for professional use including networked PCs, servers and business equipment
- ▶ Eclipse ProTel provides a fax/modem protector in addition to all the features of EclipsePro

MGE Eclipse, *your choice of surge suppressor where quality and affordability are a must.*

THE UNINTERRUPTIBLE POWER PROVIDER

M G E
UPS SYSTEMS

Characteristics	Eclipse Personal	Eclipse Pro/Protel
Clamping voltage	330 volts AC	330 volts AC
Joules	270 joules energy dissipation*	1020 joules energy dissipation*
Response time	<1 nanosecond	<1 nanosecond
EMI-RFI noise suppression	Up to 40 db	Up to 58 db
Agencies	UL 1449, 1363 listed, (cUL)	UL 1449, 1363, 1283, (497A ProTel) listed, (cUL)
Nominal ratings	120 VAC, 15A, 1800 watts, 60Hz	120 VAC, 15A, 1800 watts, 60Hz
Input and output connections	NEMA 5-15 straight plug with 4 foot cord 6 receptacles	NEMA 5-15 360° plug with 6 foot cord (6 foot single line telephone cord with Eclipse ProTel), 8 receptacles
LEDs	"Load protected" control and overload protection	"Ground OK", "load protected" (audible alarm), master on/off switch, 15A circuit breaker and thermal fuse
Dimensions (L x W x H)	11" x 2" x 1-1/4"	9-3/4" x 3-7/8" x 1-5/16"
Weight	1 pound/unit	1.5 pounds/unit
Standard package	20 per master carton	20 per master carton
Part Number	83500	Pro: 83501 / ProTel: 83502



MGE UPS SYSTEMS

USA (headquarters)
1660 Scenic Avenue
Costa Mesa, CA 92626
tel (800) 523-0142
(714) 557-1636
fax (714) 557-9788

CANADA
#9, 2798 Thamesgate Dr.
Mississauga, ON L4T 4E8
tel (905) 672-0990
(877) 672-0990
fax (905) 672-7667

ARGENTINA
Thames 91
1609 San Isidro
Prov de Buenos Aires
tel (54) 11-4766-8777
fax (54) 11-4766-6008

BRAZIL
Avenida Guido
Caloi 1985 (GALPAO 23)
Guarapiranga
Sao Paulo - SP, CEP 05802
tel (55) 11-5515-9255
fax (55) 11-5515-9250

MEXICO
Ave. Congreso de la
Union
#524 Colonia Santa Anita
Mexico D.F 08300
tel 525 538 9687
fax 525 530 7625

www.mgeups.com
info@mgeups.com

SPL 108
Effective: June 2003

THE UNINTERRUPTIBLE POWER PROVIDER