RACK-220G/221G 2U 6-slot Full-size Rackmount Chassis





Features

- ♦ RoHS compliant design
- ♦ 2 x USB on front panel
- ♦ 2 x 8cm cooling fans with easy replaceable fan filter
- ♦ 1 x 5.25", 1 x front accessible 3.5", 1 x 3.5" HDD





RACK-220GW / 221GW

RACK-220GB / 221GB

Specifications

◆ Construction	Heavy duty metal		
♦ SBC Form Factor	Full-size, slot CPU card		
	1 x 5.25"		
♦ Drive Bays	1 x front accessible 3.5"		
	1 x 3.5" HDD		
♦ Cooling Fans	2 x 8cm		
♦ I/O Ports	2 x USB		
♦ Expansion Slots	6 slots		
♦ Indicators	Power, HDD		
♦ Buttons	Power switch, reset		
♦ Operating Temperature	0~50°C		
♦ Operation Humidity	10% ~ 90%		
♦ Color	W:White / B:Black		
♦ Weight (Net/ Gross)	8.2 kg / 12.4 kg		
◆ Dimensions (DxWxH)	487.5mm x 431mm x 88 mm		

Ordering Information


Part No.	Description
RACK-220G C /ACE-832AP	2U 6-slot full-size rackmount chassis for PICMG 1.0 SBC, with ACE-832AP-RS, RoHS $$
RACK-220G C ATX /ACE-832AP	2U rackmount chassis for micro-ATX motherboard, with ACE-832AP-RS, \ensuremath{RoHS}
RACK-221G C /ACE-832AP	2U 6-slot full-size rackmount chassis for PICMG 1.3 SBC, with ACE-832AP-RS, RoHS $$

Color Code: B-Black W-White

Selection Guide

Model No.	SBC Type	PSU Type	Color Options
RACK-220G C	PICMG 1.0	PS/2	black / white
RACK-220G CATX	micro-ATX MB	PS/2	black / white
RACK-221GC	PICMG 1.3	PS/2	black / white

Dimensions



Backplane Options

Model No.	000 T	DOL	PCI ISA	PCle		PSU	
Wodel No.	SBC Type	PCI		x1	х4	x16	Connector
PCI-5SDA-RS-R301	PICMG 1.0	L2+R2	0	0	0	0	AT/ATX
PCI-5SD5-RS -R301	PICMG 1.0	L2+R2	0	0	0	0	AT
PCIAGP-5SD-RS -R301	PIAGP	L2+R1	0	0	0	0	ATX
PCI-6SD-RS-R30 ¹	PICMG 1.0	L1+R1	L1+R1	0	0	0	ATX
PE-6SD ²	PICMG 1.3	0	0	3	0	1	ATX
PE-6SD2 ²	PICMG 1.3	1	0	2	0	1	ATX

¹Backplanes for RACK-220G ²Backplanes for RACK-221G

Power Supply Options

	i	
Туре	Model No.	Watt
AT	ACE-925AP-U-RS	250W
AI	ACE-935AL-RS	300W
ATX	ACE-832AP-RS	300W
AIX	ACE-841AP-S-RS	400W

RACK-220G/221G can support single PS/2 PSU. For more models of IEI PSU, please visit www.ieiworld.com