

# V E N U S

## 3.5" Aluminum External Enclosure

Cypress CY7C68300A (ATA-6)

Oxford 911 (ATA-6)

USB2.0 / FireWire / Combo



# DS3

### Features

Cableless Connection Interface  
Silent operation with embedded 80mm cooling fan  
Adjustable Power Inlet (universal alignment for all IDE drives)  
Dynamic AirFlow Technology (DAT) provides optimal heat dissipation

### Expandable

Stackable, Hot-Swappable, Stands vertically and horizontally  
Daisy-Chain up to 62 hard drive devices via Firewire ports or  
up to 127 USB 2.0 devices via USB 2.0 hubs.

### MODELS

DS-2316SATABK  
(Black/SATA)

DS-2316B2BK  
(Black/USB2.0)

DS-2316CBK  
(Black/USB2.0+FW)

### Performance

Sustained transfer rate (maximum):

- USB2 -- 34 MB/sec
- FireWire -- 40 MB/sec

Bus transfer rate (maximum):

- USB2 -- 480 Mb/sec
- FireWire -- 400 Mb/sec

### Environmental Specifications

Operating temperature: 5° C to 40° C

### Windows System Requirements

Pentium II-class equivalent processor or later  
Windows 98SE, Me, 2000 Professional, or XP  
CD-ROM drive  
32 MB RAM or more as required by Windows  
Available FireWire/1394/i.LINK (OHCI-compliant),  
USB 1.1/2.0 port or SATA port

### Macintosh System Requirements

iMac, power Macintosh G3 or later models  
Mac OS 9.0 or higher  
CD-ROM drive  
32 MB RAM or more as required by Mac OS  
Available FireWire/1394/i.LINK (OHCI-compliant) USB 1.1  
or 2.0 port

### Drive Configuration

Support 3.5" IDE ATA 100/133 HDD (USB2.0 / FW / Combo)  
Support 3.5" SATA-to-SATA HDD (DS-2316SATA model only)

### Physical Specifications

Dimensions: 8 x 5.2 x 2 inches (206 x 132 x 50 mm)  
Weight: 1.5 lbs, (0.5 Kgrams)  
Material: Aluminum Frame / Plastic Tray  
Cooling: 80mm x1 (Internal Tray)

### Power Requirements

AC Input Voltage: 100 ~ 240V/12V-1.7A VAC  
Input Frequency: 47 ~ 63 Hz AC

### Package Contents

VENUS DS3 - 3.5" Aluminum External Enclosure  
User's Manual  
Software driver (only for USB2.0 / USB2.0+FW)  
AC adapter, Data Cable(s)  
Mounting Accessories