

# V E N U S

5.25" Aluminum External Enclosure

Cypress CY7C68300A (ATA-6)

OxFord 911 (ATA-6)

USB 2.0 / FireWire / Combo



DS5

## Features

Silent operation with embedded 40mm cooling fan  
Built-in 3.5" mount (No rails needed)  
Dynamic AirFlow Technology (DAT) provides optimal heat dissipation



## Expandable

Stackable, Hot-Swappable, Stands vertically and horizontally  
Daisy-Chain up to 62 hard drive devices via FireWire ports or  
up to 129 USB 2.0 devices via USB 2.0 hubs.



## Performance

Sustained transfer rate (maximum):  
- USB2 -- 34 MB/sec  
- FireWire -- 40 MB/sec

Bus transfer rate (maximum):  
- USB2 -- 480 Mb/sec  
- FireWire -- 400 Mb/sec

## MODELS

DS-2512B2BK  
(Black/USB2.0)

DS-2512B2  
(Silver/USB2.0)

DS-2512CBK  
(Black/USB2.0+FW)

DS-2512C  
(Silver/USB2.0+FW)

## Environmental Specifications

Operating temperature: 5° C to 40° C

## Windows System Requirements

Pentium II-class equivalent processor or later  
Windows 98SE, Me, 2000 Professional, or XP  
CD-ROM drive  
32 MB RAM or more as required by Windows  
Available FireWire/1394/i.LINK (OHCI-compliant),  
USB 1.1/2.0 port

## Macintosh System Requirements

iMac, power Macintosh G3 or later models  
Mac OS 9.0 or higher  
CD-ROM drive  
32 MB RAM or more as required by Mac OS  
Available FireWire/1394/i.LINK (OHCI-compliant)  
or USB 1.1 or 2.0 port

## Drive Configuration

Support CD-R, CD-RW, DVD, DVD-RW, MO..etc (USB2.0+FW)  
Built-in mount for 3.5" HDD (USB2.0+FW)

## Physical Specifications

Dimensions: 10 x 6.6 x 2.4 inches (258 x 168 x 60 mm)  
Weight: 2 lbs, (1.22 Kgrams)  
Material: Aluminum Frame / Metal Tray  
Cooling: 40mm x1 (Rear)

## Power Requirements

AC Input Voltage: 100 ~ 240V/12V-1.7A VAC  
Input Frequency: 47 ~ 63 Hz AC

## Package Contents

VENUS DS5 - 5.25" Aluminum External Enclosure  
User's Manual  
Software driver (only for USB2.0 / USB2.0+FW)  
Slim AC adapter, Data Cable(s)  
Mounting Accessories