



CRT Series SyncMaster™ 750s

Defy the Ordinary™
the ordinary™

- **17" CRT**
(16" viewable image size)
- **0.23mm H-pitch**
- **1280 x 1024 @ 65 Hz max. resolution**
- **Digital user control**
- **UltraClear™ High Contrast ARAS coating**
- **Plug & Play**
- **EnergyStar/Energy 2000**

*M*ake your office or home workspace better than ever—even if they're the same place. The SyncMaster 750s delivers the technology and value you need to excel. With a 17" UltraClear ARAS screen that delivers razor-sharp graphics and text, the 750s gives you a new perspective on creating spreadsheets, playing PC games, or even balancing your checkbook. Easy-to-use functions and advanced on-screen controls make it simple to execute any application with precision and ease. Plus, an optional 4-port USB hub lets you configure your workstation effortlessly.

The 750s combines advanced technology with benefits like power savings, Plug and Play technology and the latest user safety measures, like MPR-II compliance, for a monitor that delivers value and performance. With 1280 x 1024 maximum resolution and 0.23mm H-pitch, even the smallest details will pop with color and clarity. In addition, the 750s has a compact, ergonomic design that fits virtually anywhere. Experience the exceptional performance of the 750s today.



MODEL# 750s

CRT

Size	17" Diagonal
Viewable Image Size	16.0"
Dot Pitch	0.26mm (0.23mm, Horizontal)
Surface Treatment	Non-Glare, Multi-Layer Coated, High Contrast ARAS
Deflection	90°

Resolution

Recommended	1024 x 768 @ 85 Hz
Maximum	1280 x 1024 @ 65 Hz

Bandwidth

Maximum	110 MHz
---------	---------

Auto-Scan Frequency

Horizontal	30-70 KHz
Vertical	50-160 Hz

Display Area

Normal	312mm x 234mm
Maximum	325mm x 244mm

Microprocessor

Factory Preset Mode	8 Modes
User Mode	8 Modes

User Controls

Digital	Position, Size, Pincushion, Trapezoid, Pin Balance, Zoom, Rotation, V-Linearity, H-Moiré, V-Moiré, Parallelogram, Recall, Color Temperature, Video Input Level, Manual Degauss, Contrast, Brightness, Control Lock, Half Tone, 9 Languages
---------	--

Power

Voltage	90-264 Volts AC, 60/50 ± 3 Hz, Universal Power
---------	--

Plug & Play

DDC1/2B/2Bi

Signal Input

Connector	15-Pin Female
-----------	---------------

Display Color

Color Temperature	9300°K / 6500°K
-------------------	-----------------

Compatibility

IBM	VGA2, 720 x 400 @ 70 Hz VGA3, 640 x 480 @ 60 Hz
VESA	640 x 480 @ 75, 85 Hz 800 x 600 @ 75, 85 Hz 1024 x 768 @ 60, 75, 85 Hz 1280 x 1024 @ 60 Hz

Regulations

Safety	UL, CSA, TUV, IEC950, Scandinavian, KOREA
EMI/Emissions	FCC, DOC, CE, VCCI, KOREA, MPR-II

Dimensions

Unit (W x H x D)	15.7" x 16.2" x 15.7"
with stand	(398.8mm x 411.5mm x 398.8mm)

Weight

33.1 lbs.
(15.01 kg)

Power Management

EPA, NUTEK, VESA DPMS, Energy 2000

Casing

Available in Black or Ivory

Warranty

3 Years Part and Labor; 3 Years CRT

Included Items

Natural Color™ Color Matching Software

Optional Accessories

Samsung SyncMaster USB (self-powered with 1D4U ports) device that attaches to the base of the monitor; Part Number: UH41510/XAA
Mac Adapter available free upon request
Multimedia speaker stand; Part Number SP-5303N