



SyncMaster™ 955DF

- DynaFlat Technology— visually and physically flat
- 19" CRT (18" viewable image size)
- 0.20 mm Super Fine Pitch (H)
- 1600 x 1200 @ 68 Hz Max. Resolution
- SMART III Coating
- Super Pigment Phosphors
- High Focus Electron Gun
- Plug and Play
- Display Doctor™ On-screen Control


Go ahead, stare all you want —your work never looked as good as it will on the Samsung SyncMaster 955DF. Whether your work is graphic design, charts and graphs, or web research, you'll see it more clearly on this truly flat display. And, it's easy on the eyes—to keep you working right to the end of the day.

Super Pigment Phosphors, 0.20mm(H) Super Fine Pitch, SMART III coating and High Focus Electron Gun create razor

sharp, distortion free images, and brilliant color. And because there's no horizontal or vertical curvature on the screen, your viewing comfort and enjoyment continues through extended periods of use. So, work and surf away as long as you like. Choose the monitor you can really stare at, SyncMaster 955DF.

SyncMaster™ 955DF


Why it looks flat




0.20 mm Super Fine Pitch (H)



Super Pigment Phosphor



High Contrast Smart III Coating



High-Focus Electron Gun



Samsung Electronics America, Inc.
Information Systems Division
85 W. Tasman Drive
San Jose, CA 95134
1-800-SAMSUNG
Visit our home page at
www.samsungmonitor.com



© 2000 Samsung Electronics America, Inc.
Design and Specifications are subject to change without notice. All brand, product, service names and logos are Trademarks and/or Registered Trademarks of their respective manufacturers and companies.
Use of Energy Star Logo, other names and logos are not considered to be a product endorsement.
This device complies with FCC Class B, UL and CSA.
USA sales only
Printed in USA 955DF - 03/00

MODEL#:	PG19JSBL
CRT:	Infinite Flat Tube, 90° Deflection
Size	19"
Viewable	18.0"
Dot Pitch	0.20 mm (Horizontal Pitch)
Screen	Smart III Screen Coating (high contrast, anti-static & anti-glare)
CRT Type	Infinitely Flat Invar Shadow Mask
Resolution:	
PC Maximum	1600 x 1200 at 68 Hz Refresh Rate
PC Optimum	1280 x 1024 at 75 Hz Refresh Rate
MAC Maximum	1600 x 1200 at 65 Hz Refresh Rate
MAC Optimum	1280 x 1024 at 80 Hz Refresh Rate
Pixel Frequency:	135 MHz
Scanning Frequency:	
Horizontal	30-85 kHz
Vertical	50-160 Hz
Controls:	
Digital (On-Screen Display)	Contrast, Brightness, Horizontal Position, Vertical Position, Horizontal Size, Vertical Size, Barrel, Pincushion, Pin Balance, Trapezoid, Parallelogram, Rotation, Zoom In/Out, Focus, Clear Moiré, Color Mode Select, Hue, V-Linearity, Saturation, Language Select, Sync Select, Video Level, Recall, Save, Manual Degauss
Microprocessor:	
Factory Preset Mode	8
User Mode	10
Plug & Play:	DDC 1/2 Bi
Power:	90-264 Volts AC, 60/50 Hz, Universal Power
Power Consumption:	
Normal	110 Watts
Maximum	130 Watts
Power Management:	VESA DPMS, Energy Star, NUTEK
Signal Input:	
	Separate H/V Sync
	Composite Sync
	Sync on Green
Cable	15-Pin D-Sub Connector
Environmental Considerations:	
Operating Temperature	32° F to 104° F
Humidity	10% to 80%, non-condensing
Dimensions:	
Unit (W x H x D) with stand	18.4" x 19.0" x 18.3"
Box (W x H x D)	22.5" x 22.8" x 22.8"
Weight:	
Net/Shipping	51.8 lbs / 61.3 lbs.
Safety:	
Safety	UL, CSA, TUV, IEC 950, DHHS 21 CFR, CCIB, PTB, SEMKO, NEMKO, DEMKO, SETI, EIAJ, NOM, PCBC, EZU, MEEI, GOST, SISIR CPA, SIQ
EMC	MPR-II, CE, FCC B, DOC, VCCI
Ergonomics	EN50081-(1-2), BCIQ, RFS GS ZHI, ISO 9241
Warranty:	3 years P & L; 3 years CRT
Optional Accessories:	Samsung SyncMaster USB Hub (self powered with 4 ports) device that attaches to the base of the monitor; Part Number: UH41510/XAA